
VIII-1230 VERTICAL MAST SERIES SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM



STANDARD FEATURES

- ▶ Electric drive
- Proportional controls
- ▶ Tool tray
- ▶ Flashing beacon
- Motion alarm
- ▶ Slide out extension
- Compact design
- Active load-sensing
- Active tilt alarm
- ▶ 15 A charger
- > Saloon doors
- No folding rails

▶ Removable platform controls

- Non-slip deck
- Electric brakes
- Automatic pothole protection
- ▶ Onboard diagnostic display
- ▶ Non-marking tires
- ▶ Emergency lowering system
- Liftable with forklift or crane
- ► CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

NSI A92.20


PRELIMINARY BROCHURE SUBJECT TO CHANGE




SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

SPE	CIFICATIONS		
A	Working Height (2 person indoor/1 person outdoor)	19.2 ft	6 m
В	Platform Height Maximum (2 person indoor/1 person outdoor)	13.2 ft	4 m
C	Platform Height Minimum	23.6 in	0.6 m
D	Ground Clearance Elevated	0.67 in	1.7 cm
E	Ground Clearance Lowered	3.1 in	8 cm
F	Machine Length	54.7 in	1.39 m
G	Overall Width	30 in	0.76 m
н	Stowed Height	68.5 in	1.74 m
1	Platform Length	52 in	1.32 m
J	Platform Width	30 in	0.76 m
К	Slide Out Extension Deck Length	16 in	0.41 m
	Wheelbase	41.7 in	1.06 m
	Tires	11.8 x 2.9 in	0.3 x 0.1 m

PERFORMANCE				
Rated Occupancy (Indoor/Outdoor)	2/1 Person(s)			
Platform Capacity	529 lbs	240 kg		
Slide Out Extension Deck Capacity	220 lbs	100 kg		
Gradeability		%		
Inside Turn Radius	0 in	0 cm		
Drive Speed Elevated (Proportional)	0.3 mph	0.5 km/h		
Drive Speed Lowered (Proportional)	3.1 mph	5 km/h		
Working Slope	2°/2	2 °/ 2 °		
Weight	2006 lbs	910 kg		
POWER				
Hydraulic Tank Capacity	1.7 gal	6.5 L		
Batteries	4 x 6 V 2	4 x 6 V 225 Ah		





A