

HY-BRID LIFTS™
BY CUSTOM EQUIPMENT LLC



HB-1030CE

SELF-PROPELLED AERIAL WORK PLATFORM

FEATURES & SPECIFICATIONS

HB-1030CE

LARGE WORK PLATFORM

Includes 76.2 cm slideout deck extension for extra supplies and work space, extension is supported mid-rail to eliminate jams.

COUNTER ROTATING WHEELS

Will not cause carpet to buckle, helps protect sensitive floors and prevent surface scuffs on job site.

LOW STOWED HEIGHT

Low entry height allows for easy loading of materials and tools onto the platform.

LOW FLOOR LOADING

Lightweight design allows for use on delicate or sensitive surfaces.

USER-FRIENDLY DESIGN

Low step height and full swing gate provide easy access to platform and reduce chances of knee and neck strain.

ROBUST RAIL SYSTEM

Unique rail technology provides greater durability and resilience against wear on the job site.

OVERSIZED 3.18 CM PINS

Robust scissor stack requires no greasing and oversized pins reduce scissor sway.

NON-MARKING WHEELS

Protect sensitive floors and prevent surface scuffs on job site.

NON-SKID DECK

Large durable platform provides safe and ample working area.



HEIGHTS

| | |
|--------------------------|---------|
| Working Height | 5.0 m |
| Platform Height Max | 3.0 m |
| Platform Height Min | 62.1 cm |
| Ground Clearance Raised | 1 cm |
| Ground Clearance Lowered | 7.6 cm |

METRIC

MEASUREMENTS

| | |
|--------------------|----------|
| Overall Length | 176.5 cm |
| Overall Width | 76.2 cm |
| Stowed Height | 172.7 cm |
| Platform Length | 152.4 cm |
| Platform Width | 63.5 cm |
| Platform Extension | 76.2 cm |

PERFORMANCE

| | |
|---------------------|--------------|
| Platform Capacity | 340.2 kg |
| Rated Occupancy | 2 person |
| Extension Capacity | 113.4 kg |
| Weight | 751.8 kg |
| Gradeability | 25% |
| Inside Turn Radius | 53.3 cm |
| Drive Speed Raised | 0.3 m/s |
| Drive Speed Lowered | 1.1 m/s |
| Lift Speed Up/Down | 15/16 sec |
| Power Source | (2) 12V DC |
| Tires Front/Rear | 25.4/25.4 cm |

FLOOR LOADING

| | |
|------------------|-----------|
| Min Wheel Load | 557.8 kPa |
| Max Wheel Load | 809.4 kPa |
| Min Machine Load | 6.0 kPa |
| Max Machine Load | 8.7 kPa |

1-866-334-0756 // WWW.HYBRIDLIFTS.COM

This brochure is for illustrative purposes only and based on the latest information available at the time of printing. Hy-Brid Lifts reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. Hy-Brid Lifts™ is a trademark of Custom Equipment, LLC. ©2018 Custom Equipment, LLC. All rights reserved.

09/17 Part No. L01-06

HY-BRID LIFTS™
BY CUSTOM EQUIPMENT LLC