

FEATURES & SPECIFICATIONS

HB-P3.6

INCREASED WORK SITE SAFETY

Sturdy and easy to operate Hy-Brid Lifts are the safe and efficient alternative to ladders or scaffolding on a job site.

COMPACT DESIGN

The HB-P3.6 is 67.6 cm wide and can easily maneuver through doors and onto standard personnel elevators.

MAINTENANCE FREE

Maintenance free AGM Battery and easy access panels improve life cycle and cost of ownership.

LOW FLOOR LOADING

Extremely lightweight design makes the lift easy to push around and allows for use on delicate or sensitive surfaces.

USER-FRIENDLY DESIGN

Low step height and full swing gate provide easy access to platform and reduce chances of knee and neck strain.

ROBUST RAIL SYSTEM

Unique rail technology provides greater durability and resilience against wear on the job site.

OVERSIZED 2.54 CM PINS

Robust scissor stack requires no greasing and oversized pins reduce scissor sway.

INTEGRATED HYDRAULIC SYSTEM

Pump and cylinder system are integrated providing less potential leak points.

TOTAL-LOCK REAR CASTERS

Prevents unwanted wheel and caster rotation

AUTO-LOCK BRAKES ON FRONT TIRES

Prevents machine surfing during use.

NON-MARKING WHEELS

Protect sensitive floors and prevent surface scuffs on job site.





HEIGHTS	METRIC
Working Height	3.6 m
Platform Height Max	1.6 m
Platform Height Min	51.5 cm
Ground Clearance Lowered	6.4 cm
MEASUREMENTS	
Overall Length	104.1 cm
Overall Width	67.6 cm
Stowed Height	161.5 cm
Platform Length	94 cm
Platform Width	55.9 cm
PERFORMANCE	
Platform Capacity	226.8 kg
Rated Occupancy	1 person
Weight	260.8 kg
Lift Speed Up/Down	9/12 sec
Power Source	12V DC
Tires Front/Rear	20.3/20.3cm
FLOOR LOADING	
Min Wheel Load	792.9 kPa
Max Wheel Load	1482.4 kPa
Min Machine Load	3.6 kPa
Max Machine Load	6.8 kPa

1-866-334-0756 // WWW.HYBRIDLIFTS.COM